

HCVR5104H-V2



HDCVI

Technical Specifications

| System | | |
|-------------------------|--------------|---|
| Main Processor | | Embedded processor |
| Operating System | | Embedded LINUX |
| Video | | |
| Standard | | NTSC(525Line, 60f/s), PAL(625Line, 50f/s) |
| Audio | | |
| Input | | 1 channel, RCA |
| Output | | 1 channel, RCA |
| Two-way Talk | | Reuse audio input/output channel 1 |
| Display | | |
| Interface | | 1 HDMI, 1 VGA, |
| Resolution | | 1920×1080, 1280×1024, 1280×720, 1024×768, 800×600 |
| Privacy Masking | | 4 rectangular zones (each camera) |
| OSD | | Camera title, Time, Video loss, Camera lock, Motion detection, Recording |
| Recording | | |
| Video/Audio Compression | | H.264 / G.711 |
| Resolution | | 720P(1280×720/1280×600)/960H(960×576/960×480)/D1/4CIF(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120) |
| Record Rate | Main Stream: | 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps) |
| | Extra Stream | CIF/QCIF(1~25/30fps) |
| Bit Rate | | 48~6144Kb/s |
| Record Mode | | Manual, Schedule(Regular(Continuous), MD), Stop |
| Record Interval | | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec |
| Video Detection | | |
| Trigger Events | | Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips |
| Video Detection | | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank |
| Playback & Backup | | |
| Sync Playback | | 1/41/4/8 |
| Search Mode | | Time/Date, MD & Exact search (accurate to second) |
| Playback Functions | | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom |
| Backup Mode | | USB Device / Network |
| Network | | |
| Ethernet | | RJ-45 port (10/100M) |

Dimensions(mm):

